

## Electrical conductive powder hose



12\*20mm



10\*15mm/11\*16mm/12\*18mm



## Kci family replacement parts



KCI-201-R



K27

## New 2F family parts



Colo-G-2F

G91-300



G91-150



G90(2F)

## Other brand replacement



E13



N69



N70

We can produce all kinds of spare parts according to your sample or drawing. More details please contact us.

## New X1 family parts



W41



W42



W43



W44



W45



W46



W47



W48



W49



W50



Lab spray booth



COLO-S-04548-T  
(W400mm\*  
H500mm\*D 480mm)

Lab curing oven



COLO-4355-T  
(W450mm\*  
H500mm\*  
D 350mm)



Colo-S-0711  
(700width x  
1000 height x  
800 depth)



Colo-V-T2  
Portable Voltage tester



Colo-8822  
Thickness Meter



Colo-8856N  
microprocessor thickness meter



Colo-0686  
Gloss Meter

The manual coating booth COLO-S series are ideal for small batches and highest quality.

**Value • Flexibility • Performance**



**COLO-S-1517**



**COLO-S-2315**

**100% Polyester filters,  
quick-release type**



**simple PLC control unit**

## THE ADVANTAGES OF THE COLO-S BOOTH:

- Powder coated steel booth, moveable
- Delivered ready for connection
- Integrated Illumination
- Mobile powder collecting hopper
- Simplified filter cartridge for changing
- Supervision of minimal exhaust air volume

### Technical Data

### COLO-S-1517

### COLO-S-2315

No. of filter elements	2	4
Extraction volume	4000Nm <sup>3</sup> /h	6600Nm <sup>3</sup> /h
Fan power, effective	2.2kw	4.0kw
Voltage/Frequency	3x380-420V/50HZ ( or as request )	
Compressed air consumption	15Nm <sup>3</sup> /h/6bar input pressure	
Weight (approx.)	480kgs	580kgs

### Booth dimensions

Width	1500(1580) mm	2300(2550) mm
Depth	1000(2000) mm	1500(2100) mm
Height	1700(/2150) mm	1500(2240) mm